



OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on February 19, 2015.

Hydrogamma Spa
Via Delle Industrie, 2/4
20050 Sulbiate (Milano)
Italy
39 039 622 601

Facility: Milano, Italy

Mechanical Plumbing Devices

Flexible Plumbing Connectors [G]

CPWXDN A C LLL [1] SPWXDN A C LLL [2]

Hose [3] [G]

| | |
|--------------------------|--------------------------|
| PPW Inner Diameter 06 mm | PPW Inner Diameter 08 mm |
| PPW Inner Diameter 10 mm | PPW Inner Diameter 13 mm |
| SPW Inner Diameter 06 mm | SPW Inner Diameter 08 mm |
| SPW Inner Diameter 10 mm | SPW Inner Diameter 13 mm |

[1] Naming convention:
 DN - 06, 08, 10 or 13
 A and C - Connectors (any 2 combinations):
 For DN - 06: CL8, CP3/8, M3/8, M8C or M8L
 For DN - 08: CL10, CP3/8, CP1/2, CPN3/8, M3/8, M10C or M10L
 For DN - 10 and DN - 13: CP1/2, CP3/4, CPN1/2, CPN3/4, M1/2 or M3/4
 BX - Nickel plated
 LLL - Length:
 Up to 250 cm for DN - 06, 08 and 10
 Up to 200 cm for DN - 13

[2] Naming convention:
 DN - 06, 08, 10 or 13
 A and C - Connectors (any 2 combinations):
 For DN - 06: CL8, CP3/8, M3/8, M8C, or M8L
 For DN - 08: CL10, CP3/8, CP1/2, CPN3/8, M3/8, M10C, or M10L
 For DN - 10 and DN - 13: CP1/2, CP3/4, CPN1/2, CPN3/4, M1/2, or M3/4
 BX - nickel plated
 LLL - Length:
 Up to 180 cm for DN6
 Up to 135 cm for DN8
 Up to 108 cm for DN10
 Up to 80 cm for DN13

[3] Hose lengths are restricted as follows:
 Up to 180 cm for DN6
 Up to 135 cm for DN8
 Up to 108 cm for DN10
 Up to 80 cm for DN13

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.